

# KSM BLACK



- Fully rated Load Break Switch
- Good resistance against UV and many chemicals
- M20 cable glands
- Wall mounting with membrane gaskets
- Wall mounting dimensions: 62,0 x 90,0 mm
- Large cable terminals 1,5 – 16 mm<sup>2</sup>
- Padlockable handle to OFF-position
- Handle sealable to ON-position
- Enclosure can be sealed to any position
- Available as 2, 3, 4P and 3P with auxiliary contact (1NO)
- Large 1,5 – 16 mm<sup>2</sup> neutral and earth terminals on 3P switch, earth on 2P and 4P switches

GTIN	Type	Poles	AC-23 240 V	AC-23 400/415 V
6419410265543	KSM 216 BB M1 2XM20P	2	16 A / 3 kW	-
6419410265550	KSM 225 BB M1 2XM20P	2	25 A / 4 kW	-
6419410265567	KSM 316 BB M1 2XM20P	3	-	16 A / 7,5 kW
6419410265574	KSM 325 BB M1 2XM20P	3	-	25 A / 11 kW
6419410265581	KSM 416 BB M1 2XM20P	4	-	16 A / 7,5 kW
6419410265598	KSM 425 BB M1 2XM20P	4	-	25 A / 11 kW
6419410265604	KSM 316S BB M1 2XM20P	3 + 1NO	-	16 A / 7,5 kW
6419410265611	KSM 325S BB M1 2XM20P	3 + 1NO	-	25 A / 11 kW
6419410265628	KSM 316S BB M1 3XM20P	3 + 1NO	-	16 A / 7,5 kW
6419410265635	KSM 325S BB M1 3XM20P	3 + 1NO	-	25 A / 11 kW

**KATKO KSM now available as  
black!**